

CheckMK: Execute Service Discovery

19.03.2026 21:47:35

FAQ-Artikel-Ausdruck

Kategorie:	Server-Dienste::Dienstüberwachung	Bewertungen:	0
Status:	öffentlich (Alle)	Ergebnis:	0.00 %
Sprache:	en	Letzte Aktualisierung:	16:24:39 - 04.02.2026

Schlüsselwörter

Dienstüberwachung CheckMK Monitoring

Lösung (öffentlich)

Attention For service discovery to be successful, the CheckMK agent must be correctly installed on the respective host. Please refer to the following instructions depending on the operating system:

- [1]Windows
- [2]Linux

By normal means, it is not necessary to perform a service discovery manually. A CheckMK background process periodically checks all hosts for new or vanished services/checks and automatically applies the appropriate changes.

Service Discovery

Within the detailed view of a host you can access "Service Discovery" via the menu item "Host" and then "Run service discovery":

On the following page, you can request a new service scan using the "Rescan" button:

Once the scan is complete, the services/checks can be activated using the green + icon or deactivated using the red x icon. We recommend making use of the "Accept all" button:

Once you have accepted or rejected the service checks, you still need to activate the change. The following section describes this procedure.

Activate changes

If you have made changes, these are initially saved in a temporary configuration. The changes itself are only applied in production when they are activated.

If changes were made, you will find a yellow icon with an exclamation mark in the top right-hand corner. Clicking on this icon will take you to the page for activating the changes:

On this page, you can activate your change by clicking on the "Activate on selected sites" button:

[1] <https://tickets.tu-dresden.de/otrs/public.pl?Action=PublicFAQZoom;ItemID=1235;Nav=>

[2] <https://tickets.tu-dresden.de/otrs/public.pl?Action=PublicFAQZoom;ItemID=1234;Nav=>