

[en] Certificate -SSL Certificate Request - CSR creation using Unix (Config-File)

23.07.2024 03:59:15

FAQ-Artikel-Ausdruck

Kategorie:	IT-Sicherheit & Anmeldung an Diensten::PKI-Zertifikate	Bewertungen:	0
Status:	öffentlich (Alle)	Ergebnis:	0.00 %
Sprache:	en	Letzte Aktualisierung:	11:37:15 - 15.07.2024

Schlüsselwörter

Zertifikat Zertifikatsbeantragung ACME CSR

Lösung (öffentlich)

CSR creation using Unix (Config-File)

Requirements:

- OpenSSL installed

1. The download of the template configuration file can be found on the right under the attachments (zih-generic-req.conf).

2. Adjust configuration file if SubjectAltNames (multiple DNS names) are to be used:

o Line 34, remove hash symbol (#) before "req_extensions = v3_req"

o Line 67, remove hash symbol (#) before "subjectAltName"

o Replace DNS names with desired parameters. The primary DNS name must also be entered. Formatting must be kept as follows: DNS:XYZ1..., DNS:XYZ2..., DNS:XYZ3....

3. Execute command in command line:

```
openssl req -new -config zih-generic-req.conf -keyout privkey.pem -outform PEM  
-out certreq.pem -nodes
```

4. The following parameters are already set and must be confirmed with [ENTER]:

Country name

Federal state

Location name

Organization name

5. The following parameters must be entered manually:

Unique DNS name: XYZ.tu-dresden.de (complete host name)

E-mail address: admin@tu-dresden.de (E-mail address of the contact person)

Note: The 'Unique DNS Name' must also be entered manually if it is already used in the SubjectAltNames

When using Wildcard entries it is recommended to register a DNS entry for wildcard for Sectigo before in the DNS

6. The directory now contains the private key (privkey.pem) and the certificate request (certreq.pem)